Device Information

```
    Page Count = 46757
    Installed Memory = 1024 MB
    Processor Speed = 1 GHz (2)
```

- Processor ID = d581894c9a2fac8b
- Serial Number = 5029944035VZW
- ✤ TLI = 42CC170

```
PID = 0301
```

VID = 043D

```
    Machine Type = 5029-438
    Asset Tag =
    Last Settings Wipe = Never
```

CALSET

```
C Developer Operating Point = 2.6000
C Laser Operating Point = 5.0000
C Linearization Stat = 1.0000
M Developer Operating Point = 2.6000
M Laser Operating Point = 4.4000
M Linearization Stat = 1.0000
Y Developer Operating Point = 2.6000
Y Laser Operating Point = 4.5000
Y Linearization Stat = 1.0000
K Developer Operating Point = 6.5000
K Laser Operating Point = 2.5000
K Linearization Stat = 1.0000
Color Alignment Stat = 1.0000
Calibration Preference = 3.0000
Temperature at Calibration = 23.0352
Humidity at Calibration = 64.5703
Last Calibration = 48286.0000
Sensor Characterization Stat = 1.0000
Sensor Hardware Stat = 1.0000
```

```
Engine ID = 35
Debug Level = Ship
Active Adapter = Ethernet
Kernel = CSNZJ.070.045
Base = CSNZJ.070.045
Engine = ZJ.070.E037
Panel = f0.12p48v3
Green Micro = v2.12
Font = 8.11H02-U7.1
Base = 01-Oct-19 07:32
Crypto Module = 3.3
Crypto Core = 2.1
Tray 1 =
Security Module = 0
```